



US008193446B1

(12) **United States Patent**  
**Taylor**

(10) **Patent No.:** **US 8,193,446 B1**  
(45) **Date of Patent:** **Jun. 5, 2012**

(54) **WALL MOUNT ELECTRICAL BOX**

(76) Inventor: **Michael J. Taylor**, South Bend, IN (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 200 days.

(21) Appl. No.: **12/545,352**

(22) Filed: **Aug. 21, 2009**

(51) **Int. Cl.**  
**H01R 13/46** (2006.01)

(52) **U.S. Cl.** ..... **174/58**; 174/50; 174/64; 439/535; 248/906

(58) **Field of Classification Search** ..... 174/58, 174/50, 59, 60, 61, 64; 220/4.02; 248/906, 248/300, 343; 52/317

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

3,620,404 A \* 11/1971 Grasso ..... 220/477  
D406,070 S 2/1999 Thomas

5,998,746 A 12/1999 Clark  
6,969,800 B1 \* 11/2005 Liao ..... 174/50  
7,105,742 B1 \* 9/2006 Jolly ..... 174/50  
7,173,184 B2 \* 2/2007 Hull et al. .... 174/58  
7,238,882 B2 7/2007 Perkins et al.  
7,405,374 B2 7/2008 Thomas et al.


\* cited by examiner


*Primary Examiner* — Dhiru R Patel  
(74) *Attorney, Agent, or Firm* — Botkin & Hall, LLP


(57) **ABSTRACT**

An electrical box mountable within a wall and installable from outside the wall. The box has a pan that includes a front flange for contacting an outer wall surface that extends outwardly from a sidewall. A back bracket is positioned opposite the front flange and adjacent to the back wall and a fastener having a shaft extends through the back wall to movably secure the back bracket to the back wall. No portion of the shaft extends behind the back bracket. The back bracket is movable relative to the pan between a first position adjacent to the back wall and a second position spaced farther from the back wall. The bracket and front flange are adapted for clamping a portion of a wall located between the front flange and back bracket when the back bracket is in its first position.

**7 Claims, 5 Drawing Sheets**














FIG. 4





1

**WALL MOUNT ELECTRICAL BOX**

## BACKGROUND OF THE INVENTION

Connections made within walls must be made within electrical junction boxes and the space within a wall is frequently an obstacle in installing a standard electrical box. Electrical boxes must be used to make electrical connections even when mechanical features within the wall make using the box inconvenient. Such mechanical features may include ductwork or plumbing pipes. Often times an electrician installing an electrical box does not have an opportunity to provide input as to the location of such mechanical features and must work around them. In such situations where an electrician works on a job after finish contractors have installed wallboard or other wall covering material, the electrician must work within the confines of the situation he finds. In cases where plumbing or ductwork is behind the location where an electrical fixture is desired to be placed, moving the location of the electrical box to another location may not be an option.

Shallow electrical boxes exist for challenging installations that require working in locations where mechanical obstructions prevent installing an electrical box extending deep within a wall. Typically, existing electrical boxes have threaded fasteners such as screws that protrude into the wall and a screwdriver is used to turn heads located on the outwardly facing side of the box. Turning the screws usually causes tabs to extend outwardly to clamp the wall from behind, or some toggle part within the wall is used to attach the box to the wall. If such a box were to be removed, it would not be possible to retrieve the tabs or toggle parts within the wall because these parts will fall to the bottom of the wall as the screws are removed. Additionally, the screws in existing boxes usually extend behind the deepest part of the box within the wall. While an existing electrical box may be shallow, the attaching screws may extend into the wall much deeper, thus creating the potential to damage mechanical features within the wall.

## SUMMARY OF THE INVENTION

The present invention is an electrical box that is mountable within a wall and may be installed from outside the wall. The electrical box has a pan that includes a front flange for contacting an outer wall surface that extends outwardly from a sidewall. A back wall spans across the sidewall to define an interior. A back bracket is positioned opposite the front flange and adjacent to the back wall and a fastener having a shaft extends through the back wall to movably secure the back bracket to the back wall. No portion of the shaft extends behind the back bracket. The back bracket is movable relative to the pan between a first position adjacent to the back wall and a second position spaced farther from the back wall. The bracket and front flange are adapted for clamping a portion of a wall located between the front flange and back bracket when the back bracket is in its first position.

In another aspect of the invention the fastener includes threads on its shaft for receiving a nut, and the nut urges the back bracket against the portion of the wall between the front flange and back bracket as the nut is tightened against the back wall.

In the case where a plurality of fasteners are used, the fasteners are spaced from the sidewall to permit an end of the back bracket outside of the wall to be inserted into an opening in the wall that is substantially the same size as the exterior of the sidewall when the wall is located between the back wall and the back bracket.

2

When the fasteners are screws, the heads of the screws are the only portion of the fastener that extends behind the back bracket.

## BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of the electrical box of this invention installed in a wall as viewed from behind;

FIG. 2 is a perspective view of the electrical box shown in FIG. 1 from in front of the box, outside the wall;

FIG. 3 is a perspective of the electrical box shown in FIGS. 1 and 2 outside of the wall;

FIG. 4 is a top sectional view of the electrical box shown in FIGS. 1-3 showing the electrical box outside the wall;

FIG. 5 is a top sectional view of the electrical box shown in FIGS. 1-4 with the wall between the back wall of the pan and back bracket;

FIG. 6 is a top sectional view of the electrical box shown in FIGS. 1-5 with the box installed in the wall; and

FIG. 7 is another embodiment of the electrical box having a flat back bracket.

## DETAILED DESCRIPTION OF INVENTION

The electrical box **10** of this invention is particularly suited to being mounted into a wall **12** from outside the wall **12** in situations where an obstruction on the inside of the wall **12** would prohibit protrusions from extending behind the electrical box **10**. The wall **12** has wallboard **13** having an outer surface **14** and an inner surface **16**. The interior **18** of the wall **12** is considered to be behind the electrical box **10**.

The electrical box **10** includes a pan **20** that has a front flange **22** that extends outwardly from a sidewall **24**. A back wall **26** spans across the sidewall **24** to form an interior **28**. The pan **20** may be made of metal that is stamped and may also be a molded plastic part. The front flange **22** is designed to contact an outer surface **14** of a wall **12** in which the electrical box **10** will be mounted.

A back bracket **30** is positioned opposite the front flange **22** and is held near the back wall **26** with two screws **32**. The back bracket is a metal piece that is longer than the width of the exterior of the sidewall **24** of the pan **20**. The back bracket **30** may be made as shown in FIG. 3, where the ends **34** of the bracket **30** are bent toward the front flange **22**. Another back bracket **30'** is a continuous flat piece and its ends **34'** that are not bent.

The screws **32** are threaded into the back bracket **30** and tightened into the back bracket **30**. The screws **32** remain fixed relative to the back bracket **30** and move with the back bracket **30**. Their threaded shafts **36** protrude through the back wall **26** into the interior **28** of the pan **20**. The threaded shafts **36** slide freely through holes **37** in the back wall **26**. FIG. 3 shows how the screws **32** protrude into the interior **28** of the pan. As such, no threaded portion of the screws **32** extends behind the back bracket **30**.

The screws **32** receive nuts **33** on their shafts **36**. The back bracket **30**, **30'** has a first position shown in FIGS. 6, and 7 that is adjacent to the back wall **26** of the pan **20**. The back bracket **30**, **30'** also has a second position spaced farther from the back wall **26** than in the first position and this is shown in FIG. 4. Since the shafts **36** of the screws **32** slide freely through the holes **37**, the back bracket **30** is movable between the first and second positions. The lengths of the screws **32** are chosen so that when the nuts **33** are near the ends of the shafts **36**, the wallboard **13** will fit between the back wall **26** and back bracket **30** as shown in FIG. 5.

3

When an electrician installs the electrical box he will first cut a round opening **40** in the wallboard **13** that is the same size or slightly larger than the exterior surface of the sidewall **24** of the pan **20**. Cutting the opening **40** is typically done with a standard hole saw. As is frequently the case, the opening **40** reveals a pipe **44** in the wall **12** where the electrical box **10** is to be placed. As seen in FIGS. 4-6, this pipe **44** would obstruct the placement of a standard electrical box. Once the opening **40** is cut, the nuts are backed off the screws so that the back bracket **30** is in its second position spaced away from the back wall **26**. The electrical box **10** is then placed as shown in FIG. 5, with the wallboard **13** between the back bracket **30** and the back wall **26**. Once the back bracket **30** is behind the wallboard **13**, the electrical box is moved over as shown in FIG. 6 so that the wallboard **13** is between the front flange **22** and the back bracket **30**. To complete the installation, the nuts **33** are tightened against the back wall **26**, which urges the back bracket **30** toward the back wall **26** and clamps the portion of the wallboard **13** that is between the back bracket **30** and front flange **22**. This installed position corresponds to the first position of the back bracket **30** relative to the back wall **26**, where the back bracket **30** is relatively near the back wall **26**. In this position, the ends **34** being bent as shown in FIG. 6 allow the depth of the pan **20** to extend further into the wall than the thickness of the wallboard **13**.

The invention is not limited to the details given above, but may be modified within the scope of the following claims.

What is claimed is:

1. A wall mount electrical box comprising:  
a pan having a front flange for contacting an outer wall surface, a periphery sidewall, and a back wall spanning across said sidewall to define an interior, said front flange extending outwardly from said sidewall; and  
a back bracket positioned opposite said front flange and adjacent to said back wall, a fastener fixed relative to said

4

back bracket and having a shaft extending through said back wall movably securing said back bracket to said back wall so that no portion of said shaft extends behind said back bracket, said back bracket movable relative to said pan between a first position adjacent to said back wall and a second position spaced farther from said back wall, said back bracket and said front flange adapted for clamping a portion of said wall located between said front flange and back bracket when said back bracket is in its first position.

2. A wall mount electrical box as claimed in claim 1, wherein said fastener slidingly extends through said back wall and said fastener includes threads on its shaft for receiving a nut, said nut urging said back bracket against said portion of said wall as said nut is tightened against said back wall.

3. A wall mount electrical box as claimed in claim 2, including a plurality of fasteners.

4. A wall mount electrical box as claimed in claim 3, wherein said fasteners are screws having a head, said screws mounted into said back bracket so that only said head extends behind said back bracket.

5. A wall mount electrical box as claimed in claim 3, wherein said fasteners are spaced from said sidewall to permit an end of said back bracket outside of said wall to be inserted into an opening in said wall having substantially same size as an exterior of said sidewall when said wall is located between said back wall and said back bracket.

6. A wall mount electrical box as claimed in claim 3, wherein said fasteners are screws and no part of said shaft extends behind said back bracket.

7. A wall mount electrical box as claimed in claim 2, wherein said back bracket includes ends that are bent toward said front flange.

\* \* \* \* \*