



US009057588B1

(12) **United States Patent Simpson**

(10) **Patent No.: US 9,057,588 B1**
(45) **Date of Patent: Jun. 16, 2015**

(54) **PORTABLE REMOTE-CONTROLLED TARGET**

(71) Applicant: **Randy Simpson**, Dowagiac, MI (US)

(72) Inventor: **Randy Simpson**, Dowagiac, MI (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 143 days.

(21) Appl. No.: **13/900,179**

(22) Filed: **May 22, 2013**

(51) **Int. Cl.**
F41J 1/10 (2006.01)

(52) **U.S. Cl.**
CPC **F41J 1/10** (2013.01)

(58) **Field of Classification Search**
USPC 273/403-410, 390-392, 359, 366-370
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

398,186	A *	2/1889	Reh fuss	273/404
840,610	A *	1/1907	Easdale	273/404
1,928,768	A *	10/1933	Sell et al.	273/409
1,981,293	A *	11/1934	Varrelman	273/404
2,034,839	A *	3/1936	Sheffield	273/382
2,048,155	A *	7/1936	Armantrout	273/407

2,294,730	A *	9/1942	Eggers	324/178
3,519,272	A *	7/1970	De Vogelaere	273/404
4,247,116	A *	1/1981	McQuary	273/394
4,317,572	A *	3/1982	Iseli	273/406
4,491,328	A *	1/1985	Meyer	273/403
4,523,761	A *	6/1985	Huscher	273/371
4,548,414	A *	10/1985	Denis	273/367
4,583,744	A *	4/1986	Tolliver et al.	273/404
5,169,157	A *	12/1992	Salmon	273/407
5,829,753	A *	11/1998	Wiser	273/407
6,257,584	B1 *	7/2001	Nasuti	273/407
6,543,778	B2 *	4/2003	Baker	273/407
7,374,173	B2 *	5/2008	Nasuti	273/407
8,141,878	B2 *	3/2012	Kuyl	273/403
2008/0211190	A1 *	9/2008	Smith	273/407
2009/0026708	A1 *	1/2009	Sitton	273/403
2013/0228975	A1 *	9/2013	Mason, III	273/406

* cited by examiner


Primary Examiner — Mark Graham

(74) Attorney, Agent, or Firm — Botkin & Hall, LLP

(57) **ABSTRACT**

A portable remote controlled target assembly includes a frame carried on a base. The frame includes a first arm and a second arm. A sheath is carried on the first arm, a roller is carried on the second arm, and a sheet spans the sheath and the roller. The sheet includes a target. The sheet is advanced between the sheath and the roller by a motor which rotates the roller. The motor is remote control operated to allow new targets to be displayed while a user is remotely positioned during target practice.

16 Claims, 3 Drawing Sheets






FIG.2




FIG.3




FIG. 4





FIG. 5

PORTABLE REMOTE-CONTROLLED TARGET

BACKGROUND OF THE INVENTION

Target shooting is a popular sport and past time. Target shooting generally involves firing a weapon, such as a firearm or other projectile, at a target. Following repeated use, the target generally must be replaced with a clean target. Replacing the target is generally accomplished in one of two ways, first a user must approach the target and manually replace the target, or second, the target is mechanically moved toward the firing area, whereby the user can replace the target.

Where the user must approach the target, all other shooters must hold fire during replacement of the target, which can be inconvenient for the other shooters. Further, some shooters with disabilities may not be able to approach a target.

Mechanically moved targets are typically on a pulley system or similar apparatus that carries the target to the shooter to allow the target to be replaced without other shooters having to interrupt their shooting. Mechanically moved targets are expensive to build, and are impractical for anything except close-range shooting.

An improved target system is desired.

SUMMARY OF THE INVENTION

The present disclosure describes a remote-controlled target assembly, suitable for target practice with firearms or other projectiles. The target assembly of the present disclosure is disassemblable for transport and storing. The target of the present disclosure is capable of remote operation, such that the target can be replaced without having a user approaching the target and without having to advance the target to the user.

The present disclosure describes a target assembly supported on a base and having a frame extending above the base. The frame includes a pair of arms spaced apart from one another, the arms supporting a target. The target extends between a pair of rollers, with one of the rollers connected to a motor, with the motor remote-control activated. When activated, the motor rotates one of the rollers causing the target to be wound around the roller, thereby advancing the roll and providing a new target.

Once disassembled, the target assembly folds flat for convenient storage, such as for transportation.

BRIEF DESCRIPTION OF THE DRAWINGS

A preferred embodiment of this invention has been chosen wherein:

FIG. 1 is a perspective view of the target assembly of the present disclosure;

FIG. 2 is a front view of the target assembly of FIG. 1;

FIG. 3 is a top view of the target assembly of FIG. 1;

FIG. 4 is a top view of the target assembly of FIG. 1 and showing detail of the rollers; and

FIG. 5 is a perspective view of the target assembly of FIG. 1 as disassembled.

DESCRIPTION OF THE PREFERRED EMBODIMENT

The present disclosure describes a target assembly 10 which is formed having a base 12 and a frame 14. The target assembly 10 is a portable target suitable for target practice. One of the difficulties with target practice is the need to regularly change or replace targets. The target assembly 10 is

remote-controlled to allow new targets to be provided without a user having to be near the target assembly. The target assembly 10 is disassemblable for portability and storage.

Referring now to FIGS. 1 and 4, the base 12 of the target assembly 10 is a generally flat plate 16 having a first post 18 and a second post 20 extending from the upper face of the plate 16. The plate 16 is preferably formed from a sufficiently heavy and durable material to hold the target assembly 10 in an upright position.

The frame 14 is formed having a first arm 22 and a second arm 24 as illustrated in FIG. 1. The first arm 22 and second arm 24 are separated by a crossbar 26 and a first brace 28 and a second brace 30. The first arm 22 and second arm 24 are preferably hollow tubular members. The first arm 22 includes an opening 32 at the lower end thereof which accepts the first post 18. Similarly, the second arm 24 includes an opening 34 at the lower end thereof which accepts the second post 20. The first post 18 preferably is shaped to form a complimentary fit inside the first arm 22, such as a square cross-section as shown in FIG. 4. Similarly, the second post 20 preferably is shaped to form a complimentary fit inside the second arm 24 at the opening 34.

The first arm 22 and the second arm 24 of the frame 14 are joined together by a series of crossbars 26, 36, 38. Crossbars 36 and 38 are located near the base 12 and are oriented parallel one another and are joined perpendicularly to both first arm 22 and second arm 24. Crossbars 36 and 38 are preferably tubular members and provide strength and rigidity to the frame 14.

The first arm 22 is generally s-shaped with an upper portion 40 and a lower portion 42 which, when the frame 14 is mounted on the base 12, are oriented generally perpendicular to the base 12 and are oriented generally parallel with one another. The lower portion 42 is joined to the upper portion 40 by a spanning portion 44, wherein the spanning portion 44 is angled relative the upper portion 40 and the lower portion 44. The second arm 24 is a mirror-image of the first arm 22 with an upper portion 46, a lower portion 28 and a spanning portion 50. The crossbars 36 and 38 extend between the respective lower portions 42, 48. The crossbar 26 extends between the respective spanning portions 44, 50. The first brace 28 extends between the cross bar 26 and the upper portion 40. The second brace 30 extends between the cross bar 26 and the upper portion 46. It is contemplated that other crossbar and brace configurations are possible to serve the purpose of bracing the first arm 22 and the second arm 24. One or more brackets 52 are carried on the frame 14.

Referring now to FIG. 5, the first arm 22 includes a post 54 which extends from the end of the arm 22 opposite the base 12. The post meets the first arm 22 at a shoulder 56, the shoulder 56 forming a stepped change in outer perimeter dimension between the first arm 22 and the post 54.

Target assembly 10 also includes a sheath 58, which is carried on the post 54 as shown in FIG. 1. The sheath 58 is preferably cylindrical having a longitudinal slit 60 formed through the wall of the sheath 58 and extending the length thereof. The sheath 58 is mountable on the post 54, with the post nesting within one end of the sheath 58 and the sheath 58 abutting the shoulder 56. A roll 62 is carried in the interior of the sheath 58, the roll 62 having a sheet 64 wrapped around thereof. The sheet 64 is paper or other thin material suitable for having a target 66 displayed on the sheet and suitable for being rolled around the roll 62. Sheet 64 passes through the slit 60, such that the sheet 64 is unrollable from the roll 62 by advancing the sheet 64 out through the slit 60. One end of the sheet 64 is attached to a roller 82 which is mounted on the second arm 24.

The roller **82** is a generally cylindrical rod which includes an arm **68** extending from one end of the roller **82**. The arm **68** meets the roller **82** at a shoulder **70**, the shoulder **70** forming a stepped diameter change between the roller **82** and the arm **68**. Shoulder **70** is seated on a guide **72** which is adjacent the end of the second arm **24**. The guide **72** includes an aperture which circumscribes the arm **68**. The arm **68** includes a keyed terminus **74** which is shaped to mate with a keyed seat **76** (not shown) which is formed as part of a motor **78**. A bracket **80** is fastened to the second arm **24**. The bracket carries the guide **72** at one end and the motor **78** at the other end, thereby mounting the guide **72** and the motor **28** to the frame **14**.

The motor **78** includes an opening for accessing the keyed seat **76** (not shown). The keyed terminus **74** is sized to be seated against the keyed seat **76** (not shown) such that when the motor **78** rotates, the arm **68** in turn rotates. The motor **78** is in electrical communication with a receiver **84**. The receiver **84** includes an antenna **86** for receiving signals from a remote control **88**. The receiver **84** also serves as a power supply for the motor **78**. The receiver **84** translates the signals received from the remote control **88** into commands for operating the motor **78**.

A leading edge of the sheet **64** is attached to the roller **82**, such as by tape or adhesive. When thusly joined, when the motor **78** is activated, the roller **82** rotates and the sheet **64** is rolled around the roller while the sheet **64** is drawn out of the sheath **58** through the slit **60**. In this way, the sheet **64** moves from the sheath **58** to the roller **82**, causing the target **66** to move likewise. As such, when a user needs a new target **66**, the user uses the remote control **88** to send a signal to the receiver **84** which relays a signal to the motor **78** which rotates the roller **82** advancing a fresh target **66**.

The target assembly **10** is disassemblable, as shown in FIG. **5** for ease of transportation and storage. When disassembled, the sheath **58** is clipped to one or more of the brackets **52** and the roller is clipped to one or more other brackets **52**. A first eyelet **92** and a second eyelet **94** are formed as part of the frame **14**, preferably attached to the crossbar **26**. When disassembled, the first post **18** is threaded through the first eyelet **92** and the second post **20** is threaded through the second eyelet **94**. The frame **14** is held to the base **12** by a cotter pin **96**, preferably the cotter pin **96** is held by an aperture passing through one of posts **18**, **20** and prevents the corresponding eyelet **90**, **92** from being drawn away from the base **12** while the cotter pin **96** is in the aperture. When disassembled, a cap **98** is placed over one end of the sheath **58** to protect and secure the roll **62**.

One advantage of the target assembly **10** described herein is that since the target **66** is printed on a thin sheet **64**, the bullet or other projectile fired at the target will readily pass through the sheet **64** on contact. Since the bullet will readily pass through the sheet **64**, the kinetic energy of the bullet will not be transferred to the target assembly **10**. As such, the target assembly **10** will be suitable for all types of guns and ammunitions since the assembly **10** will not absorb the force of the projectile. This is an improvement over previous targets assemblies which include a backing which collects or slows the ammunition.

The slit **60** of the sheath **58** is preferably oriented facing normal to, or away from, the roller **82**. By orienting the slit **60** away from the roller **82**, the sheet **64** is forced into contact with an edge of the slit **60** and a portion of the face of the sheath **58**, which adds some friction to the sheet **64**, which helps to hold the sheet **64** in tension so that the sheet remains taut during use.

The sheet **64** is wrapped around a portion of the sheath **58** in such a way that the sheet **64** faces the user. Similarly, the

sheet **64** is wrapped around the roller **82** in a way that the sheet **64** faces the user. As shown in FIG. **1**, the sheet **64** includes a plurality of targets **66** printed on the sheet **64** at intervals. By wrapping the sheet **64** around the side of the sheath **58** and the roller **82** which faces the user, it is more likely that the targets **66** will be in view of the user.

The brackets **52** are preferably designed to affirmatively grasp objects. As shown in FIG. **1**, the brackets **52** include a pair of spaced apart fingers which bias toward each other such that when an object, such as roller **82** or sheath **58**, is placed between the fingers, the fingers will resistively grasp the object, thereby retaining the object to the frame **14**.

The roller **82** and the sheath **60** are preferably oriented vertically relative the base **12**. In this way, the sheet **64** extends horizontally between the sheath **60** and the roller **82**. By mounting the roller **82** and the sheath **60** in a vertical position, only gravity is needed to hold these members in place, no additional fasteners are needed which simplifies assembly and disassembly of the target assembly **10**.

It is understood that while certain aspects of the disclosed subject matter have been shown and described, the disclosed subject matter is not limited thereto and encompasses various other embodiments and aspects. No specific limitation with respect to the specific embodiments disclosed herein is intended or should be inferred. Modifications may be made to the disclosed subject matter as set forth in the following claims.

What is claimed is:

1. A target assembly, for use as a shooting target, comprising:
 - a base having a first post and a second post;
 - a frame having a first arm supported on said base at said first post and a second arm supported on said base at said second post;
 - a sheath supported on said first arm, said sheath having a slit; said sheath carrying a rolled sheet;
 - a roller supported on said second arm; said sheet extending from said sheath through said slit to said roller;
 - a motor suitable for rotating said roller;
 - a receiver in electrical communication with said motor, said receiver suitable for receiving a remote signal;
 - a target disposed on said sheet.
2. The target assembly of claim **1**, wherein said slit is oriented away from said roller.
3. The target assembly of claim **1**, and an assembled position defined by said first arm removably supported on said base at said first post, said second arm removably supported on said base at said second post, said sheath removably supported on said first arm, said roller removably supported on said second arm.
4. The target assembly of claim **3**, and a first eyelet and a second eyelet disposed on a crossbar extending between said first arm and said second arm.
5. The target assembly of claim **4**, and a first bracket carried on said frame and a second bracket carried on said frame.
6. The target assembly of claim **5**, and a disassembled position defined by said first post received in said first eyelet, said second post received in said second eyelet, said first bracket removably carrying said sheath, said second bracket removably carrying said roller.
7. A target assembly, for use as a shooting target, comprising:
 - a base having a first post and a second post;
 - a frame having a first arm and a second arm;
 - a sheath having a slit;
 - a roller;
 - a first eyelet and a second eyelet joined to said frame;

5

a first bracket and a second bracket joined to said frame; an assembled position defined by said first arm removably supported on said base at said first post, said second arm removably supported on said base at said second post, said sheath removably supported on said first arm, said roller removably supported on said second arm;

a disassembled position defined by said first post received in said first eyelet, said second post received in said second eyelet, said first bracket removably carrying said sheath, said second bracket removably carrying said roller.

8. The target assembly of claim 7, wherein said slit is oriented away from said roller.

9. A target assembly, for use as a shooting target, comprising:

- a vertically oriented roller having a sheet affixed thereto;
- a plurality of targets displayed on said sheet;
- a motor connected to said roller;
- a receiver in electrical communication with said motor;
- a remote control in communication with said receiver, whereby a signal transmitted from said remote control is relayed by said receiver to said motor to rotate said roller, thereby winding said sheet around said roller;
- a sheath carrying said sheet, wherein rotation of said motor advances said sheet from said sheath to said roller, said sheath having a slit extending the longitudinal length of

6

said sheath, said sheet passing through said slit, said slit oriented away from said roller, said sheath is slideably carried on a frame post which is disposed at the upper end of a frame member of said target assembly.

10. The target assembly of claim 9, wherein said frame member is supported on a base post which extends from a base.

11. The target assembly of claim 10, and an assembled position defined by said frame member supported on said base at said base post, said sheath removably supported on said frame post, said roller removably supported on said frame member.

12. The target assembly of claim 11, and a disassembled position defined by said base post received in an eyelet, a first bracket removably carrying said sheath, a second bracket removably carrying said roller.

13. The target assembly of claim 10, wherein said frame member is defined by a first arm and a second arm connected by a crossbar.

14. The target assembly of claim 13, wherein said frame post is disposed at one end of said first arm.

15. The target assembly of claim 13, wherein said eyelet is disposed on said crossbar.

16. The target assembly of claim 13, wherein said roller is mounted to said second arm.

* * * * *